



# LED Display Product Data Sheet LTS-4817CKS-P

Spec No. :DS30-2012-0088  
Effective Date: 01/11/2020  
Revision: A



**LED DISPLAY**  
**LTS-4817CKS-P**

**LED DISPLAY**

**LTS-4817CKS-P**

<u>Rev</u>	<u>Description</u>	<u>By</u>	<u>Date</u>
01	Preliminary Spec.	Reo Lin	08/22/2012
<b>Above data for PD and Customer tracking only</b>			
-	NPPR Received and Upload on System	Reo Lin	08/22/2012
A	Update Packing spec. in page 10	Reo Lin	01/06/2020

# LED DISPLAY

## LTS-4817CKS-P

### 1. Description

The LTS-4817CKS-P is a 0.39 inch (10.0mm) digit height single digit SMD display. This device uses AS-AlInGap Yellow LED chips (AlInGap epi on GaAs substrate). The display has gray face and white segments and suitable for reverse mount assembly.

#### 1.1 Features


- 0.39 inch (10.0 mm) DIGIT HEIGHT
- CONTINUOUS UNIFORM SEGMENTS
- LOW POWER REQUIREMENT
- EXCELLENT CHARACTERS APPEARANCE
- HIGH BRIGHTNESS & HIGH CONTRAST
- WIDE VIEWING ANGLE
- SOLID STATE RELIABILITY
- CATEGORIZED FOR LUMINOUS INTENSITY.
- LEAD-FREE PACKAGE(ACCORDING TO ROHS)

#### 1.2 Device

Part No	Description
AlInGaP Yellow	Common Anode
LTS-4817CKS-P	Rt. Hand Decimal

## LED DISPLAY LTS-4817CKS-P


### 2. Package Dimensions



#### Notes :

1. All dimensions are in millimeters. Tolerances are  $\pm 0.25$  mm (0.01") unless otherwise noted
2. Foreign material on segment  $\leq 10$  mil
3. Ink contamination (surface)  $\leq 20$  mils
4. Bubble in segment  $\leq 10$  mil
5. Bending  $\leq 1\%$  of reflector length
6. Plastic pin's burr max is 0.14 mm

### 3. Internal Circuit Diagram



### 4. Pin Connection

No	Connection
1	CATHODE E
2	CATHODE D
3	COMMON ANODE
4	CATHODE C
5	CATHODE DP
6	CATHODE B
7	CATHODE A
8	COMMON ANODE
9	CATHODE F
10	CATHODE G

# LED DISPLAY LTS-4817CKS-P

## 5. Rating and Characteristics

### 5.1. CHIP LED Absolute Maximum Rating at Ta=25°C

Parameter	Maximum Rating	Unit
Power Dissipation Per Segment	70	mW
Peak Forward Current Per Segment ( 1/10 Duty Cycle, 0.1ms Pulse Width )	60	mA
Continuous Forward Current Per Segment Derating Linear From 25°C Per Segment	25	mA
	0.28	mA/°C
Operating Temperature Range	-35°C to +105°C	
Storage Temperature Range	-35°C to +105°C	
Iron Soldering Conditions: 1/16 inch Below Seating Plane for 3 Seconds at 260°C		

### 5.2. Chip LED Electrical / Optical Characteristics at Ta=25°C

Parameter	Symbol	MIN.	TYP.	MAX.	Unit	Test Condition
Average Luminous Intensity Per Segment	IV	201	650		μcd	IF=1mA
			8450		μcd	IF=10mA
Peak Emission Wavelength	λp		588		nm	IF=20mA
Spectral Line Half-Width	Δλ		15		nm	IF=20mA
Dominant Wavelength	λd		587		nm	IF=20mA
Forward Voltage Per Chip	VF		2.05	2.6	V	IF=20mA
Reverse Current Per Segment <sup>(2)</sup>	IR			100	μA	VR=5V
Luminous Intensity Matching Ratio (Similar Light Area)	IV-m			2:1		IF=1mA






#### Notes :

1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commission International De L'Eclairage) eye-response curve
2. Reverse voltage is only for IR test. It cannot continue to operate at this situation
3. Cross talk specification  $\leq 2.5\%$

**LED DISPLAY**  
**LTS-4817CKS-P**

**5.3. Typical Electrical / Optical Characteristics Curves**


(25°C Ambient Temperature Unless Otherwise Noted)



NOTE : KS=AlInGaP YELLOW

## 6. SMT SOLDERING INSTRUCTION

(Number of reflow process shall be less than 2 times, and cooling process to normal temperature is required between the first and the second soldering process)




### Notes :

1. Recommended soldering condition

Reflow Soldering (Two times only)		Soldering Iron (One time only)	
Pre-heat:	120~150°C.	Temperature	300°C Max.
Pre-heat time:	120sec. Max.	Soldering time	3sec. Max.
Peak temperature:	260°C Max.		
Soldering time:	5sec. Max.		


2. Number of reflow process shall be less than 2 times, and cooling process to normal temperature is required between the first and the second soldering process.

## 7. Recommended Soldering Pattern




## 8. Packing Specification

### 8.1. Packing Reel Dimensions




## LED DISPLAY LTS-4817CKS-P

### 8.2. Packing Carrier Dimensions




1. 10 sprocket hole pitch cumulative tolerance  $\pm 0.20$ .
2. Carrier camber is within 1 mm in 250 mm.
3. All dimensions meet EIA-481-C requirements.
4. Thickness :  $0.40 \pm 0.05$ mm.
5. Packing length per 22" reel : 45.50 Meters.
6. Component load per 13" reel : 800 pcs.
7. Minimum packing quantity is 200 pcs for remainders

### 8.3. Trailer part / Leader part



## 9. Moisture Proof Packing

All N/D SMD displays are shipped in moisture proof package. The displays should be stored at 30°C or less and 60 % RH or less. Once the package opened, moisture absorption begins.



If the parts are not stored in dry conditions, they must be baked before reflow to prevent damage to the parts. Baking should only be done once

Package	Temperature	Time
In Reel	60°C	≥48hours
In Bulk	100°C	≥4hours
	125°C	≥2hours